## PATENT ABSTRACTS OF JAPAN

(11) Publication number:

55-069793

(43) Date of publication of application: 26.05.1980

(51)int.CI.

F04D 29/10

(21)Application number: 53-143009

F16J 15/40

(22)Date of filing:

(71)Applicant: MITSUBISHI HEAVY IND LTD

20.11.1978

(72)Inventor: KAWAGUCHI KATSUYUKI


**MIHARA MITSUO** 

## (54) SEALING SYSTEM FOR AXIS OF BLOWER FOR PRESSURE TRANSPORTATION OF **POISONOUS GAS**

## (57)Abstract:

PURPOSE: To ensure the prevention of gas leakage by controlling sealing gas pressure in conformity with the outlet pressure of an impeller.

CONSTITUTION: Approximately half of a gas used by an upper gas bearing 3a flows into a sealing chamber 9 provided between a labyrinth fin 8 and the gas bearing 3a. As the pressure difference between the pressure in the sealing chamber 9 and that at the outlet 10b stream is indicated by a manometer 16, the pressure is controlled in such a manner that the pressure in the sealing chamber 9 is higher than that at the outlet 10b of the stream, using a control valve 18. Thus the leakage of CO and other gases can be prevented certainly.



## **LEGAL STATUS**

[Date of request for examination]

[Date of sending the examiner's decision of rejection]

[Kind of final disposal of application other than the examiner's decision of rejection or application converted registration]

[Date of final disposal for application]

[Patent number]

[Date of registration]

[Number of appeal against examiner's decision of

rejection]

[Date of requesting appeal against examiner's decision of rejection)

[Date of extinction of right]

Copyright (C); 1998,2003 Japan Patent Office